



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214
 Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.
 Customer Service and Technical Service can be reached at 1-800-437-3188.

Product: **Calpar 80** Product Code: **0825P-00-S**
 Revised: 05/07/2009
 HazMat Name: Non-Regulated
 STCC: 29-114-15

| Test | Method | MIN | MAX | Typical |
|-----------------------|--------|------|------|---------|
| Viscosity, CST @ 40C | D445 | | | 14.09 |
| Viscosity, CST @ 100C | D445 | | | 3.19 |
| Viscosity, SUS @ 100F | D2161 | 75.0 | 85.0 | 78.4 |
| Viscosity, SUS @ 210F | D2161 | | | 37.0 |
| Viscosity Index | D2270 | 80 | | 83 |
| Gravity, API, 60F | D4052 | | | 33.6 |
| Flash Point, COC, C | D92 | 182 | | 188 |
| Flash Point, COC, F | D92 | 360 | | 370 |
| Pour Point, C | D97 | | -15 | -20 |
| Pour Point, F | D97 | | 5 | -5 |
| Color, ASTM | D1500 | | 0.5 | L0.5 |
| Aniline Point, C | D611 | | | 98.2 |
| Aniline Point, F | D611 | | | 208.7 |
| Saturates, Mass % | D2007 | 90.0 | | 90.5 |
| Sulfur, Mass % | D4294 | | 0.03 | 0.0019 |

Copyright 2008 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Typical values only represent the values one would expect if the property were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values are not based on a statistically relevant number of tests. The information in this document relates only to the named product. The user is solely responsible for all determination regarding any use and any process.